

arrowtrading home

Arrow Trading

Spotwelder 9000Amps

[Call for Pricing](#)

The GP9000 Spotwelder is a 9000amp spotwelder and forms part of our newest range this high quality industrial spotwelder is finally affordable to all workshops and panelshops, microprocessor control optimises the output parameters and the durable and reliable touch panel allows quick settings

Features :

1. Digitally Adjustable : electricity time, welding current etc.
2. Touch panel, durable and reliable.
3. Stable output current.
4. Microprocessor control to optimise welding parameters.
5. Can be connected to Studder kit, manual spot gun and pneumatic spot gun.
6. Continuous single spot welding and pulse single spot welding.
7. Controlled by main voltage, all spots are distributed evenly.

Important Note : The GP9900A Spot Welder requires an 60AMP 6KA circuit breaker to handle the 9000amps of Current, Please ensure that you have sufficient power at the site where the welder will be used.

Specifications:

Input Voltage : 380V 50Hz
Input Power : 15KVA
Delayed Fuse Current : 38A
No Load Voltage : 10.5V
Dimensions of Welder Only : 550 x 350 x 400mm
Electric Welding Current Range : 200 - 4000A
Single Side Spot Welding Range : 0.8 + 0.8mm
Cable Length : 1500 + 2000mm
Electric Welding Current Range : 2000 - 9900A
Allowed Welding Thickness : 2.0 + 2.0mm (1.0 + 1.0 + 1.0mm)
500mm Extended Arm Welding Thickness : 1.5 + 1.5mm
Cable Length : 1600mm
Air Pressure : > or = 6MPa

