

arrowtrading home

Arrow Trading

MIG/MAG2350 Welder

[Call for Pricing](#)

The MIG MAG gas shielded series welders can perfectly weld a variety of metals including carbon steel, alloy steel, aluminum and copper alloy, etc. Different alloy wires can be used according to the various alloy materials being welded.

Hurricane MIG/MAG-2350 Welder Specifications

Input Voltage : 380V 50Hz

Input Power : 11.1KVA

No Load Voltage : 16 - 24V

Electric Welding Current Range : 35 - 350A

Duty Cycle : 25%

Wire Spool Diameter : 15KG 300mm

Flux Core Wire : 0.8 - 1.2mm

Wire For Steel : 0.8 - 1.2mm

Wire For Stainless Steel : 0.8 - 1mm

Wire For Aluminum : 0.8mm

Insulation Class : F

Protection Degree : IP21S

Dimensions : 880 x 440 x 1000mm

Weight : 95KG

Features :

1. Perfect for thin and medium thickness sheet metal welding.
2. Spot weld two overlapped metal sheets from one side.
3. Adjusting soft start provides a smooth arc start.
4. Simple and economic wire feeder with motor
5. Automatic voltage compensation provides stable current.
6. High productivity, good quality, no spatter, or spray arc and good visibility while welding.
7. Small heated area from welding, ensures small transformation and perfect welding shape.
8. Overload protection and overheating protection.

[Vendor Information](#)