

**arrowtrading home**

*Arrow Trading*

## **HI-PRESSURE HOT WATER DIESEL FIRED UNITS**

[Call for Pricing](#)

TSI delayed total stop system with the following functions:

- \* Temporary shutdown of the machine after 30 seconds of inactivity
- \* Definitive shutdown of the machine after 20 minutes of inactivity. If there are leaks in the water circuit or if the HP nozzle is blocked.
- \* Automatic burner shut down in the absence of fuel.
- \* Detection and indication of absence of fuel.
- \* Low voltage controls to guarantee maximum user safety.
- \* 4-Pole continuous duty electric motor (1450 rpm) with thermal cutout.
- \* Crankshaft driven pump with 3 ceramic pistons and forged brass head.
- \* New high efficiency weld-free stainless steel boiler mounted on a steel plate.
- \* Steel 30m coil with double circulation of exhaust gases for improved efficiency.
- \* Durable trolley roll-formed in high density polyethylene averaging 7mm thick, resistant to corrosion, atmospheric agents and UV rays.
- \* Diesel tank, detergent tank and water tank built into the trolley.
- \* Pressure and steam phase regulation valve.
- \* Output water temperature regulation valve.
- \* Burner control device triggered in the absence of pressure.
- \* High pressure detergent delivery regulated from control panel.
- \* Descaling device as standard.

### **STANDARD EQUIPMENT:**

- \* Designed to take a hose reel (user fitted optional accessory)
- \* HP gun with heat-proof extension
- \* 10 Metre high pressure hose
- \* 70cm Stainless steel lance
- \* High pressure nozzle

### **TECHNICAL:**

Model : SYNC PLUS DS 2960T  
Pressure : 200 Bar  
Volume : 15 L/min  
Absorbed : 7.2kW 380V  
Chem Tank : 25 Litres

Cable : 5.5 Metres  
Mass : 150kg  
Dimensions L x W x H : 109 x 70 x 87cm  
Max Temperature : 140Â°C  
Fuel Consumption : 5.7kg/h  
Fuel Tank : 25 Litres  
[Vendor Information](#)